

Partners in Height Safety Solution

Model: ULMP02
Safety Harness



HEIGHT SAFETY

ABLE MULTIPURPOSE HARNESS

DESCRIPTION

ABLE Multi-Purpose Full Body Safety Harness

CAPACITY AND COLOR

WLL600kg, in Blue & Green (MBS:1500kg)

FEATURES AND BENEFITS

- 1 Medically designed for maximum moment of impact safety
- 2 Harness Design minimises wearer injury during and after fall
- 3 Pebble-weave Webbing Design provides maximum grip precluding incidental buckle slippage
- 4 Integrated Webbing strap and hardware placement minimises impact injury
- 5 Combined belay loop sub pelvic strap positioning reduces risk of throat and facial injury
- 6 Medically tested Standing Step alleviates the dangers of Suspension Trauma
- 7 Retro-reflectivity built into webbing
- 8 High Tenacity Polyester Webbing for enhanced resistance to UV and common solvents (contact ABLE help line if in doubt)
- 9 160kg Wearer capacity (combined weight of wearer; clothes and tools) when used in conjunction with a ABLE Shock Absorbing Lanyard.
- 10 Articulated chest Strap and shoulder Adjustment points, designed for female users.

APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Conned Space, Positioning Restraint, Tower Work

PRODUCT DETAILS

Quick-Fit adjustable Clip In Buckles
Integrated Suspension Trauma Strap
Shoulder Conned Space / Rescue Loops
Large Pole Strap Side Dees
Padded Shoulder Straps
Tool Belt with Hi-Comfort kidney padding
Padded legs for force dispersion at moment of fall impact

Large Dorsal Dee Ring
Front Belay Loops

Webbing Material	Polyester; 45mm; UV Resilient; Solvent Resistant; Liqui-pel water guard option available
Buckle Material	Corrosion resistant electrophoresis; high tensile light weight alloy steel
Fall Arrest Hardware	Drop Forged corrosion resistant electrophoresis high strength alloy steel
Thread	Polyester; 9.81Newtons (10kg); Extension at break 19.5%
Stitch Pattern	THETA Pattern combines 313 stitches to exceed 28kN of strength. EN and ANSI compliant colour contrast
Plastic Material	UV stabilised high density polyethylene
Weight	2.45kg
Web Tenacity	Range- Min 28kN Max 30kN
Drop Forged Dee Rings	Alloy Steel (standard): 40kN; Aluminium or Stainless Steel (option): 22kN minimum
Buckle Strength	12 to 17kN model dependant; laser etch or hard marked on buckle
Standards Compliance	ANSI Z359; EN 361; AS/NZS 1891.1;
Padding Material	Neoprene Foam Laminate

Reading of ABLE instruction manual prior to use is mandabry

Certified & approved to ANSI Z359; EN 361; AS/NZS 1891.1

We utilise a continual improvement regime product spec subject to change without notice.

Model: ULMP02



QR Buckles
(Quick Release)

